

DECLARATION OF PERFORMANCE

No.: Rimat_Rot_100_LE_2206

- (1) *Unique identification code of the product-type*
Rimat Rot 100
- (2) *Intended use/es*
**Lightweight gypsum building plaster for plastering walls and ceilings inside buildings
B4/20/2 (EN 13279-1)**
- (3) *Manufacturer*
**Saint-Gobain Rigips GmbH
Schanzenstr. 84
D-40549 Düsseldorf**
- (4) *Authorised representative*
N/A
- (5) *System/s of AVCP*
System 4
- (6a) *Harmonised standard*
EN 13279-1:2008
- Notified body/ies*
Internal
- (6b) *European Assessment Document*
N/A

European Technical Assessment
N/A

Technical Assessment Body
N/A

Notified body/ies
N/A



(7) Declared performance/s


| Essential characteristics | Performance |
|--|-------------|
| Reaction to fire (R2F) (for unprotected installation situations) | A1 |
| Airborne sound insulation (R) | NPD |
| Thermal resistance (R) | NPD |

(8) Appropriate Technical Documentation and/or Specific Technical Documentation
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 28. January 2022



Raimund Heini, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

CE

**Saint-Gobain Rigips GmbH
Schanzenstr. 84
D-40549 Düsseldorf**

13

Rimat_Rot_100_LE_2206

EN 13279-1:2008

**Lightweight gypsum building plaster for plastering walls
and ceilings inside buildings
B4/20/2 (EN 13279-1)**

Notified body/ies: N/A

Reaction to fire (R2F)
(for unprotected installation situations) A1

Airborne sound insulation (R) NPD

Thermal resistance (R) NPD

